

Congratulations on purchasing your IntelliSwitch^{\mathbf{M}} IS-IW Heated towel rail timer, allowing you to reduce your power consumption and your power bill.

Features

• Cyclic mode turns towel rails on and off twice/day.

Modes (settings)

 Towel rail mode switches appliances on 4 hours and off 8 hours on a continuous cycle

Who should install an IntelliSwitch™?

We recommend installation by a **registered electrician**. Dangerous voltages (230VAC) are present on the product and in the house cabling. No responsibility will be taken by eSource Products Ltd for damages or injury caused by incorrect installation or installation by an unqualified person/s.

Ratings

Operational voltage	100-240 VAC @ 50-60 Hz
Load capacity	3A Res. 240VAC
Operating Temp	-10°C to 30°C
Compliance	AS/NZS 3100:2002
	AS/NZS CISPR 14,2002
Timer option	Cycle 4hrs on 8hrs off cont.

Installation instructions

- Electrically isolate the existing towel rail isolation switch by switching off mains to the entire house at the fuse box.
- 2. Remove the screw cover of the existing switch, and unscrew the mounting screws.
- Before unwiring the existing plate, look to see how the existing switch is wired to the house wiring.


Identify the phase (red) and neutral (black) wires from the house, and the phase (red or brown) and neutral (black or blue) coming from the towel rail element. Label them if needed.

Attach the supplied 3 wires from the IntelliSwitch $^{\mathrm{IM}}$ as shown.

Wire in the switched house phase (red) & neutral (black) cables to the corresponding red and black wires coming out of the IntelliSwitch $^{\text{TM}}$.

Connect the towel rail element brown wire to the brown wire coming out of the IntelliSwitch $^{\mathbb{N}}$. Connect the towel rail element blue wire to the common neutral from the house wiring (black wire). Earth wires can be connected together with a screw connector (not supplied).

Lastly carefully place the IntelliSwitch™ inside the flush box and re attached the isolating switch to the wall.



User Instructions

How to set towel rail/cyclic setting - on for 4 hrs and off for 8 hrs continuously

Decide when you want the cycle to start (i.e. setting it at 6pm at night turns the appliance on from 6-10pm and 6-10am everyday) and set the IntelliSwitch™ on at that time.

 Turn the IntelliSwitch™ on by turning on your existing isolating switch. The IntelliSwitch™ starts counting the on hours immediately and your towel rail is now on.

Warranty

IntelliSwitch™ switches are warranted against manufacturing faults for 2 years from date of purchase. eSource Products Ltd. is only liable for replacement or repair of the faulty unit and is not liable for any subsequent damages caused or costs incurred. Refer any servicing questions to the supplier you bought it from or call 0800 ESOURCE-(3768723).

Made in NZ by eSource Products Ltd 24F Morrin Rd Panmure Auckland Ph 09 5276655 Fax 09 5276656